

Mobil bockkran stål , spann 2,0 m



Last kap. kg	Spann (m)	Höjd (m)	Bredd (m)	Vikt (kg)	Art.nr
250	2	2	1	98	1.250.G2020
	2	3	1.5	134	1.250.G2030
	2	4	2	208	1.250.G2040
	2	5	2.5	255	1.250.G2050
	2	6	3	302	1.250.G2060
500	2	2	1	120	1.500.G2020
	2	3	1.5	166	1.500.G2030
	2	4	2	213	1.500.G2040
	2	5	2.5	310	1.500.G2050
	2	6	3	523	1.500.G2060
1000	2	2	1	125	1.1000.G2020
	2	3	1.5	171	1.1000.G2030
	2	4	2	358	1.1000.G2040
	2	5	2.5	441	1.1000.G2050
	2	6	3	690	1.1000.G2060
2000	2	2	1	138	1.2000.G2020
	2	3	1.5	209	1.2000.G2030
	2	4	2	369	1.2000.G2040
	2	5	2.5	590	1.2000.G2050
	2	6	3	701	1.2000.G2060

* Priserna är exkl. lyftdon, balkvagn, kabel och strömskena. Ytbehandling: målat



Mobil bockkran stål, spann 3,0 m



www.interlift.se
010-188 22 00



Last kap. kg	Spann (m)	Höjd (m)	Bredd (m)	Vikt (kg)	Art.nr
250	3	2	1	110	1.250.G3020
	3	3	1.5	146	1.250.G3030
	3	4	2	220	1.250.G3040
	3	5	2.5	267	1.250.G3050
	3	6	3	474	1.250.G3060
500	3	2	1	112	1.500.G3020
	3	3	1.5	176	1.500.G3030
	3	4	2	222	1.500.G3040
	3	5	2.5	315	1.500.G3050
	3	6	3	528	1.500.G3060
1000	3	2	1	143	1.1000.G3020
	3	3	1.5	189	1.1000.G3030
	3	4	2	376	1.1000.G3040
	3	5	2.5	458	1.1000.G3050
	3	6	3	708	1.1000.G3060
2000	3	2	1	152	1.2000.G3020
	3	3	1.5	226	1.2000.G3030
	3	4	2	385	1.2000.G3040
	3	5	2.5	606	1.2000.G3050
	3	6	3	716	1.2000.G3060

* Priserna är exkl. lyftdon, balkvagn, kabel och strömskena. Ytbehandling: målat

Mobil bockkran stål, spann 4,0 m



Last kap. kg	Spann (m)	Höjd (m)	Bredd (m)	Vikt (kg)	Art.nr
250	4	2	1	127	1.250.G4020
	4	3	1.5	163	1.250.G4030
	4	4	2	214	1.250.G4040
	4	5	2.5	284	1.250.G4050
	4	6	3	386	1.250.G4060
500	4	2	1	160	1.500.G4020
	4	3	1.5	224	1.500.G4030
	4	4	2	270	1.500.G4040
	4	5	2.5	364	1.500.G4050
	4	6	3	576	1.500.G4060
1000	4	2	1	180	1.1000.G4020
	4	3	1.5	225	1.1000.G4030
	4	4	2	412	1.1000.G4040
	4	5	2.5	494	1.1000.G4050
	4	6	3	744	1.1000.G4060
2000	4	2	1	226	1.2000.G4020
	4	3	1.5	300	1.2000.G4030
	4	4	2	458	1.2000.G4040
	4	5	2.5	679	1.2000.G4050
	4	6	3	790	1.2000.G4060

* Priserna är exkl. lyftdon, balkvagn, kabel och strömskena. Ytbehandling: målat



Mobil bockkran stål, spann 5,0 m



www.interlift.se
010-188 22 00

Last kap. kg	Spann (m)	Höjd (m)	Bredd (m)	Vikt (kg)	Art.nr
250	5	2	1	178	1.250.G5020
	5	3	1.5	214	1.250.G5030
	5	4	2	288	1.250.G5040
	5	5	2.5	335	1.250.G5050
	5	6	3	437	1.250.G5060
500	5	2	1	179	1.500.G5020
	5	3	1.5	244	1.500.G5030
	5	4	2	290	1.500.G5040
	5	5	2.5	383	1.500.G5050
	5	6	3	595	1.500.G5060
1000	5	2	1	214	1.1000.G5020
	5	3	1.5	260	1.1000.G5030
	5	4	2	446	1.1000.G5040
	5	5	2.5	529	1.1000.G5050
	5	6	3	778	1.1000.G5060
2000	5	2	1	255	1.2000.G5020
	5	3	1.5	329	1.2000.G5030
	5	4	2	487	1.2000.G5040
	5	5	2.5	708	1.2000.G5050
	5	6	3	819	1.2000.G5060

Mobil bockkran stål, spann 6,0 m

250	6	2	1	196	1.250.G6020
	6	3	1.5	232	1.250.G6030
	6	4	2	306	1.250.G6040
	6	5	2.5	353	1.250.G6050
	6	6	3	455	1.250.G6060
500	6	2	1	198	1.500.G6020
	6	3	1.5	262	1.500.G6030
	6	4	2	308	1.500.G6040
	6	5	2.5	401	1.500.G6050
	6	6	3	613	1.500.G6060
1000	6	2	1	284	1.1000.G6020
	6	3	1.5	300	1.1000.G6030
	6	4	2	516	1.1000.G6040
	6	5	2.5	640	1.1000.G6050
	6	6	3	848	1.1000.G6060
2000	6	2	1	357	1.2000.G6020
	6	3	1.5	431	1.2000.G6030
	6	4	2	588	1.2000.G6040
	6	5	2.5	809	1.2000.G6050
	6	6	3	920	1.2000.G6060

* Priserna är exkl. lyftdon, balkvagn, kabel och strömskena. Ytbehandling: målat

010 – 188 22 00 | WWW.INTERLIFT.SE

VÄND DIG MED FÖRTROENDE TILL INTERLIFT AB -
ETT STARKT VAL NÄR DET GÄLLER LYFT- OCH MATERIALHANTERING